

DRP PERFECT

FarmaX



The spader for livestock farms, horticulture and small-scale agriculture, with a capacity of 80 to 120 HP.



Video clip



The Farmax DRP Perfect is a medium-class spader, perfectly suited for horticulture, tree nurseries and agriculture on lighter soils.

This spader comes in various working widths and can easily be fitted with a hydraulically adjustable rotary harrow, rotary cultivator, ring roller, tube roller or packerwals. Regardless of the soil type, the DRP Perfect guarantees you the best bed for sowing or planting!

Digging and sowing in one operation

The DRP Perfect can be combined with a sowing machine so as to perform all the required operations in one step. The sowing machine is easily attached using a number of fixed mounting points, but you can also opt for a top-mounted lift to bring the sowing machine closer to the tractor. These combination possibilities help to save fuel.

www.farmax.info

DRP PERFECT

FarmaX



The PE covering prevents the machine getting blocked up. With this spader, structural damage, such as a plough pan or compaction of the subsoil, is a thing of the past. Altogether, this results in a 10-20% increase in crop yield.

Drive to main axle (rotor): Transmission case with differential

Capacity: Up to 2,96 acres (1.2 hectare) per hour in optimum conditions

Power take-off revs: 540 r.p.m.

Tractor power: 80 to 120 HP

Versatile and easy to maintain

The spader is designed for perfect ease of maintenance. It also incorporates inspection hatches in the chain case for easy monitoring of the condition of the chain transmission.

Thanks to the compact structure of the DRP Perfect, the machine's centre of gravity lies close to your tractor.

Advantages

- easily combined with other machinery
- high capacity
- compact, low-maintenance and user-friendly design
- PE coverage to prevent blockage
- suitable for multiple soil types, from sand to light clay




Compact construction



Option: Top-mounted lift



Combination with sowing machine and top-mounted lift



High-yield transmission case

Technical Data

type	operating width	max. operating depth	standard weight	required power kW/HP	number of spades
DRP 185	72.83" - 185 cm	17.72" - 45 cm	2,204 Lbs - 1.000 kg	41/55	15
DRP 215	84.65" - 215 cm	17.72" - 45 cm	2,480 Lbs - 1.125 kg	45/60	18
DRP 245	96.46" - 245 cm	17.72" - 45 cm	2,866 Lbs - 1.300 kg	50/68	18
DRP 275	108.27" - 275 cm	17.72" - 45 cm	3,141 Lbs - 1.425 kg	55/75	21
DRP 300	118.11" - 300 cm	17.72" - 45 cm	3,968 Lbs - 1.800 kg	60/80	24

www.farmax.info