# RAPIDE





A fast spader with operational span of 9.84 feet (3 m) to 13.12 feet (4 m), specially designed for heavy sand and clay soils.



Video clip



The Farmax Rapide tills heavy sand, clay and even stony soils quickly and without problems. The Rapide is a very heavyweight design and has PE plating to prevent clogging of the machinery.

With an operating span of 9.84 feet (3 m) to 13.12 feet (4 m), the Rapide gives fantastic results, even at high speeds. A really fast spader!

### Comes as standard with numerous options

The Rapide is equipped as standard with a hydraulically adjustable rotary harrow, a packer roller, a ring roller or a rotary cultivator. It is even possible to fit a second hydraulically adjustable roller for even better results on any soil type. Thanks to the many possible combinations, the machine has a high capacity and can reduce fuel consumption by up to 40%.

## RAPIDE





### **Combi-scrapers**

The specially designed combi-scrapers ensure that soil adhesion (which mainly occurs with clay soils) is prevented. The Rapide improves the soil structure and the soil quality. This increases crop yields by 10 to 20%.

**Drive to main axle (rotor):** sprocket wheel transmission **Capacity:** Up to 4,9 acres (2 hectares) per hour in optimum

conditions

**Power take-off revs:** 1.000 r.p.m. **Tractor power:** 200 to 300 HP

## **Advantages**

- very rapid rotavation with retention of quality
- problem-free tillage on heavier soil types
- reduced fuel consumption, thanks to the many possible combinations
- combi-scrapers or a better rotavation result
- many combinations possible at the same time
- very user-friendly and easy to maintain



Tilling depth up to 16.69" (50 cm)



Spading under all circumstances



Intermediate drive for narrow transport width



Attachment with shear bolts

### **Technical Data**

type	operating width	max. operating depth	standard weight	required power kW/HP	number of spades
Rapide 300	118.11" - 300 cm	16.69" - 50 cm	6,503 Lbs - 2.950 kg	115/150	24
Rapide 350	137.8" - 350 cm	16.69" - 50 cm	7,220 Lbs - 3.275 kg	130/170	30
Rapide 400	157.48" - 400 cm	16.69" - 50 cm	8,046 Lbs - 3.650 kg	148/200	30